




DIMENSIONS (Inches)

SIZE	A	B	C	D	E	F	G	AA	AA1	BB	BB1	GG	GG1	BYPASS SIZE	WT (lbs)	ACT. MODEL	TURNS TO OPEN
14	15.00	1.38	21.00	12	1.13	18.75	-	8.00	-	52.87	-	24.00	-	-	1,000	IS5 2:1	104
16	16.00	1.44	23.50	16	1.13	21.25	-	8.00	-	51.45	-	24.00	-	-	1,150	IS5 2:1	104
18	17.00	1.53	25.00	16	1.25	22.75	-	12.00	-	58.67	-	24.00	-	-	1,325	IS7 3:1	192
20	18.00	1.65	27.50	20	1.25	25.00	-	12.00	-	58.86	-	24.00	-	-	2,050	IS7 3:1	192
24	20.00	1.88	32.00	20	1.38	29.50	-	12.00	-	62.86	-	24.00	-	-	2,750	IS7 3:1	228
30	26.50	2.22	38.75	28	1.38	36.00	34.94	14.00	30.44	80.33	14.75	24.00	10.00	4	5,250	IS11 6:1	588
36	30.75	2.47	46.00	32	1.63	42.75	42.44	14.00	36.94	90.00	19.00	24.00	12.00	6	7,200	IS11 6:1	684
42	36.00	2.63	53.00	36	1.63	49.50	52.13	16.00	45.38	111.00	22.50	32.00	14.00	8	15,070	IS12 8:1	800
48	36.00	2.81	59.50	44	1.63	56.00	52.38	16.00	45.63	114.00	22.50	32.00	14.00	8	15,500	IS12 8:1	800
54	48.00	3.13	66.25	44	2.00	62.75	52.38	16.00	45.63	114.00	22.50	32.00	14.00	8	16,300	IS12 8:1	800

NOTE:

1. FLANGES CONFORM TO ANSI B16.1 CLASS 125
2. COLD WORKING PRESSURE - 250PSI
3. HYDROSTATIC TEST PRESSURE - 500PSI
4. SIDE BYPASS OPTIONAL - 30" & LARGER

DESCRIPTION:

14"-54" AWWA C515 - 125# Flanged Resilient Wedge Gate Valve with Spur Gear (NRS)

DATE:

06/10/2026

DRAWING:

RW-DD0014-A

MPi MCWANE
PLANT & INDUSTRIAL

McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234

CLOW
VALVE CO.

