




DIMENSIONS (Inches)																		
SIZE	A	B	C	D	E	F	G	X	X1	BB	BB1	GG	GG1	HH	BYPASS SIZE	WT (lbs)	ACT. MODEL	TURNS TO OPEN
14	15.00	1.38	21.00	12	1.13	18.75	-	46.77	-	9.50	-	24.00	-	48.74	-	1,000	IB5 2:1	104
16	16.00	1.44	23.50	16	1.13	21.25	-	45.33	-	9.50	-	24.00	-	47.30	-	1,150	IB5 2:1	104
18	17.00	1.53	25.00	16	1.25	22.75	-	53.60	-	10.40	-	24.00	-	55.58	-	1,325	IB7 3:1	192
20	18.00	1.65	27.50	20	1.25	25.00	-	53.80	-	10.40	-	24.00	-	55.76	-	2,050	IB7 3:1	192
24	20.00	1.88	32.00	20	1.38	29.50	-	57.73	-	10.40	-	24.00	-	59.76	-	2,750	IB7 3:1	228
30	26.50	2.22	38.75	28	1.38	36.00	29.63	71.60	25.13	14.90	14.75	24.00	10.00	74.00	4	5,250	IB11 6:1	588
36	30.75	2.47	46.00	32	1.63	42.75	37.38	81.30	31.70	14.90	19.00	24.00	12.00	83.70	6	7,200	IB11 6:1	684
42	36.00	2.63	53.00	36	1.63	49.50	43.56	98.50	36.81	19.28	22.50	32.00	14.00	101.06	8	15,070	IB12 8:1	800
48	36.00	2.81	59.50	44	1.63	56.00	46.75	101.50	40.00	19.28	22.50	32.00	14.00	104.06	8	15,500	IB12 8:1	800
54	48.00	3.13	66.25	44	2.00	62.75	46.75	101.50	40.00	19.28	22.50	32.00	14.00	104.06	8	16,300	IB12 8:1	800

NOTE:

1. FLANGES CONFORM TO ANSI B16.1 CLASS 125
2. COLD WORKING PRESSURE - 250PSI
3. HYDROSTATIC TEST PRESSURE - 500PSI
4. BOTTOM BYPASS OPTIONAL - 30" & LARGER

DESCRIPTION:

14"-54" AWWA C500 - 125# Flanged Resilient Wedge Gate Valve with Bevel Gear (NRS)

DATE:

06/10/2026

DRAWING:

RW-DD0015-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234

CLOW
VALVE CO.

